

**GRANPAPEL SAS** NIT:811.044.289-2 TEL:(574)235 4433

Type: UWF9000D Silver grey window film

## Window Film Technical Information

| Specification  | Description  |                                    |
|----------------|--|------------------------------------|
| PVC            | Туре   | Calendered monomeric soft PVC film |
|                | Thickness  | $100\pm10$ um                      |
|                | Color Code   | Silver Grey                        |
|                | Shrinkage  | ≦0.8%                              |
|                | Surface Tension  | ≥30dn/cm                           |
|                | Opacity  | >80%                               |
| Adhesive       | Туре   |                                    |
|                |  | Permanent, clear acrylic adhesive  |
|                | Weight(g/m²)   | $25\pm 2$                          |
|                |  | 15°C~40°C                          |
|                | Adhesion Temperature   |                                    |
|                | 180°   | ≥7N/25mm (FTM1)                    |
|                | Peeling Force  |                                    |
|                |  | ≥5N/25MM*25MM                      |
|                | Initial Tack   | (FTM9)                             |
|                | Holding Power  | ≥3000min (FTM8)                    |
| Liner          | Туре   | Single Side PE coated Kraft Paper  |
|                | Color  | white                              |
|                | Weight   | 140g±5g/m²                         |
|                | Release Force  | 0.05~0.2N/25MM                     |
| Storage Period | 12 months under ordinary condition at temperature of 22 °C and relative humidity of 50-55% |                                    |
| Application    | For glass decoration or masking, can be cutt on cutting plotter according to your design.  |                                    |